

PROJECT:		
ITEM #		QTY:
MODEL #_		
AIA #	SIS #	

# REMOTE CONDENSER

### RC100C49




### **Features and Benefits**

- Weather Resistant design improving operating parameters.
- · Vertical air discharge.
- Easy assembly and flexible installation with precharged line-sets or noncharged, partially assembled line-sets.
- Efficient PSC motor reduces energy usage.
- Constructed from corrosion-resistant galvanized steel.
- Remote systems reduce air conditioning requirements and cost.
- Condenser fan is located outside, ensuring quieter interior operation for customers.
- Remote condenser for CIM0530R49 models.
- Pairs with precharged linesets: RL49-25, RL49-40, and RL49-75.

# CUL US CUL Energy Verified

**IMPORTANT:** Do not route a line set that rises, then falls, then rises. Do not route a line set that falls, then rises, then falls. See diagram below.



### **Equivalent Run Calculation Example: Rise**

Calculated line set length = (Rise x 1.7) + (Drop x 6.6) + Horizontal Run Calculated line set length =  $(35 \times 1.7) + (0 \times 6.6) + 40$  Calculated line set length = 99.5 ft

Calculated line set length must not exceed 100 ft

### Warranty

• 3 years parts and labor

### **Options & Accessories**

- Precharged Lineset Options: RL49-25, RL49-40, RL49-75
- Noncharged linesets: KRL-25, KRL-40, & KRL-75

11100 E. 45th Avenue • Denver, CO 80239

Phone: 1.866.PURE.ICE www.iceomatic.com Rev. 09/2025 Printed in U.S.A.


APPROVAL: DATE:




## RC100C49

Line drawing note: Numbers with quote symbol " are in inches. Numbers enclosed in [brackets] are in millimeters.


### **PLAN / TOP VIEW**



### **ELEVATION / FRONT VIEW**




### **SIDE VIEW**




### **BOTTOM VIEW**

### **LINE SETS**



### Remote Condenser

- Remote Condenser Electrical, 7/8" Hole, Must Be Liquid Tight Connection
- B. Remote Condenser Discharge Line, INLET, 1/2" male quick connect for line set
- C. Remote Condenser Liquid Line, OUTLET, 3/8" male quick connect for line set
- D. Mounting Holes, 1/2" Hole (4)



SPECIFICATIONS		
Model	RC100C49	
Condensing Type	Remote	
Min. Circuit Amp	2	
Refrigerant	R449A	
Refrigeration Charge	16 oz	
Fan Watts	93	

OPERATING REQUIREMENTS				
	MINIMUM	MAXIMUM		
Ambient Temp. Range Air	-20°F (-29°C)	120°F (48.9°C)		

Unit Width	29 in.	737 mm	
Unit Depth	31 in.	787 mm	
Unit Height	34.5 in.	876 mm	
Shipping Weight	91 lbs / 41 kg		
Shipping Dimensions (in.)	32 (W) x 34 (D) x 28 (H)		
Shipping Dimensions (mm)	812.8 (W) x 863.6 (D) x 711.2 (H)		

Rev. 09/2025 Printed in U.S.A. 11100 E. 45th Avenue • Denver, CO 80239 • Phone: 1.866.PURE.ICE • www.iceomatic.com

