



# ELEVATION SERIES CUBE ICE MAKER

## CIM0530/0535

**Ice-O-Matic**  
Ice. Pure and Simple

### Model:

- CIM0530
- CIM0535



Energy Star Certified  
on certain models



CIM0530  
ON B55



**Safelce**

\*Available for factory or field install

## Features and Benefits

- 30" (768 mm) wide space-saving design.
- Produces up to 586 lbs (266 kg) of ice per day.
- *Energy and Environment*
  - Exceeds 2018 DOE (Department of Energy) regulations.
  - Up to 20% more energy efficient than other models.
  - Environmentally friendly, including BPA-free plastic and recyclable parts.
- *Sanitation*
  - Plastic Food Zone eliminates hard-to-clean nooks and crannies, allowing for effortless wipe down and easy, long-lasting sanitation.
  - Built in Agion® ensures unbeatable antimicrobial protection.
  - Smart LED light indicates machine status and when cleaning is required.
  - Simple, one-touch controls for sanitization and descaling.
  - BPA-free snap-in, snap-out dishwasher-safe components.
- *Unique Dual Exhaust* - Air-cooled machines are designed to discharge hot air from both the side and top of the unit, increasing installation flexibility and reducing the potential of obstructed exhaust.
- *Universal Smart Harness™* control board simplifies installation and servicing with better access, digital diagnostics, universal components and common configuration.

Safelce Purification System is an add-on option for CIM machines that destroys Coronavirus, Flu, Odors, Mold and other biological contaminants, increasing the life of the machine by up to 30%.



<https://www.youtube.com/watch?v=toReJT8QG6A&t=7s>

CIM0530/0535 CUBE ICE MAKER

## Ice Form

FULL CUBE DIMENSIONS	
W x D x H (in.)	7 <sup>5</sup> / <sub>8</sub> x 7 <sup>5</sup> / <sub>8</sub> x 7 <sup>5</sup> / <sub>8</sub>
W x D x H (mm)	22 x 22 x 22
HALF CUBE DIMENSIONS	
W x D x H (in.)	3 <sup>5</sup> / <sub>8</sub> x 7 <sup>5</sup> / <sub>8</sub> x 7 <sup>5</sup> / <sub>8</sub>
W x D x H (mm)	10 x 22 x 22



**CUBE**

## Bin Chart Kits for Combining Wider Bins with Smaller Models

		ICE STORAGE BINS										
		Model No.	B25	B40	B42	B55	B700	B110	B1000	B1300	B1325	B1660
		Capacity	242 lbs (110 kg)	344 lbs (156 kg)	351 lbs (160 kg)	510 lbs (232 kg)	680 lbs (308 kg)	854 lbs (388 kg)	1,000 lbs (454 kg)	1,320 lbs (599 kg)	1,325 lbs (601 kg)	1,660 lbs (753 kg)
		Width	30 in (762 mm)	30 in (762 mm)	22 in (559 mm)	30 in (762 mm)	30 in (762 mm)	48 in (1,219 mm)	48 in (1,219 mm)	48 in (1,219 mm)	60 in (1,524 mm)	60 in (1,524 mm)
Kits	CIM0530	Kit Not Required		N/A		Kit Not Required		BPF-1		Hold Down Securement Recommended		
	CIM0535											

\*See Ice-O-Matic Price List for Adapter Kits to combine ice makers with most available ice/beverage dispensers.

## Options & Accessories

WATER FILTERS		
Ice Machine Model	Manifold	
	System	Replacement
CIM0530	IFQ1-XL	IOMQXL (1)
CIM0535		

Note: All modular cube CIM units can be installed with manufacturer approved ozone delivery systems.

## Ice Maker Warranty

COMMERCIAL WARRANTY	
<b>Ice Maker</b>	<b>3 YEARS</b> parts and labor
<b>Evaporator and Compressor</b>	<b>5 YEARS</b> parts
<b>Evaporator</b> (when enrolled in our filter program)	<b>7 YEARS</b> parts and labor





# ELEVATION SERIES CUBE ICE MAKER

## CIM0530/O 535





CIM0530/O535 CUBE ICE MAKER

### Air Cooled

Please note: air-cooled units require 6" (152 mm) clearance for air intake and exhaust.

- A. Ice maker potable water in, 3/8" FPT.
- B. Ice maker water out, 3/4" FPT.
- C. Hole for electrical connections, 7/8".
- D. Electrical connection junction box, 7/8".


Dual Exhaust for Installation Flexibility



Air Cooled

### Water Cooled/Remote Cooled

- A. Ice maker potable water in, 3/8" FPT.
- B. Ice maker water out, 3/4" FPT.
- C. Hole for electrical connections, 7/8".
- D. Electrical connection junction box, 7/8" (remote).
- E. Condenser water in, 3/8" FPT (water only).  
Discharge line, 1/2" male quick connect coupling for precharged line set (remote only).
- F. Condenser water out, 1/2" FPT (water only).
- G. Liquid line, 3/8" male quick connect for precharged line set (remote only).



Water Cooled/Remote Cooled

### Operating Requirements

	MINIMUM	MAXIMUM	
		60 Hz	50Hz
Ambient Temp. Range Air	50°F (10°C)	100°F (38°C)	110°F (43°C)
Water Temp.	40°F (4.4°C)		
Water Pressure	20 PSIG (1.4 BAR)	80 PSIG (5.5 BAR)	
Remote Condenser Temp.	-20°F (-29°C)	120°F (50°C)	

### Dimensions

ALL MODELS	
W x D x H (in.)	30.25 x 24.25 x 21.25
W x D x H (mm)	768 x 616 x 540

### Specifications

Model Number	Cond. Unit	Ice Production* per 24hrs		Water Usage gallons per 100 lbs of ice 90°F air/70°F water		kWh Used per 100 lbs of ice @ 90°F air/70°F water	Voltage Characteristics	Min. Circuit Ampacity	Max Breaker Size	Approx. BTUs per hour	
		70°F air/50°F water lbs (kg)	90°F air/70°F water lbs (kg)	Potable	Condenser						
CIM0530A	Air	561 (254)	420 (190)	19.9	N/A	5.5	115/60/1	17.8	30	6,252	
CIM0530R**	Remote	570 (259)	405 (183)	19.6	N/A	6.3		20.1			
CIM0530W	Water	586 (266)	470 (213)	20.0	181	4.7		17.4			
CIM0535A	Air	529 (240)	425 (193)	20.0	N/A	6.1	220-240/50/1	11.2	16		
CIM0535R***	Remote	500 (227)	400 (181)	20.0	N/A	6.3		12.0			20
CIM0535W	Water	531 (241)	476 (216)	19.5	190	5.0		11.0			
CIM0535A-49	Air	522 (237)	416 (189)	18.0	N/A	5.9		11.2		16	

\* Daily ice production based on half cube configuration. When installing a CIM on a drink dispenser, the KCUBEDISPB MUST be used.

\*\* Remote model CIM0530R requires the RC100C40 / RCA1001 remote condenser.

\*\*\* Remote model CIM0535R requires the RC106C40 / RCA1061 remote condenser.

Number of Wires: 3 (including ground)

Approx. Shipping Weight lbs (kg): CIM0530A 155 (70.3) • CIM0530R 160 (72.5) • CIM0530W 155 (70.3) • CIM0535A 155 (70.3) • CIM0535R 160 (72.5) • CIM0535W 155 (70.3)

### REFRIGERANT:

Models ending in -49 are R449A, all other models are R404A  
CIM0535A = R404A • CIM0535A-49 = R449A